

S E C R E T 192332Z

[] CITE []

33721

[] LOGS-SUPPLY

REF: []

BT
[Signature]

25X1A
25X1A

25X1A
25X1A

WE WILL BE SHIPPING YOU WITHIN A FEW DAYS 220 GALLONS OF JENNITE J-16 SEALER AND 55 GALLONS OF PRIMER J-220 WHICH IS REQUIRED FOR APPLYING THIS MATERIAL TO CONCRETE FLOORS. DETAILED SHIPPING INFO WILL BE PROVIDED. THIS MESSAGE IS TO GIVE YOU APPLICATION INSTRUCTIONS WHICH ARE NOT AVAILABLE IN A COMPANY BULLETIN BECAUSE JENNITE IS NOT USUALLY USED ON CONCRETE. THE FIRST STEP IS TO REMOVE ALL GREASE, OIL AND LOOSE DIRT THIS MUST BE VERY THOROUGHLY DONE TO INSURE THAT THE JENNITE WILL STICK. AFTER THE FLOOR IS DRY APPLY THE PRIMER, THIS IS A LIGHT WEIGHT MATERIAL AND CAN BE APPLIED WITH A BACK PACK SPRAYER WHICH WE WILL FURNISH. ONLY ONE COAT OF PRIMER IS REQUIRED AND IT WILL GO ON AT ABOUT ONE GALLON TO 300 SQ FT. APPLY JENNITE THE NEXT DAY. TWO THIN COATS ARE REQUIRED AND AT LEAST 24 HOURS IS NORMALLY REQUIRED BETWEEN COATS. JENNITE IS APPLIED WITH SQUEEGEES WHICH WE WILL PROVIDE. THE RATE OF APPLICATION IS ABOUT ONE GALLON PER 100 FT SQ PER COAT. WAIT UNTIL THOROUGHLY DRY BEFORE USING FLOOR. FINAL DRYING TIME IN MOST AREAS IS 24 HRS BUT THE MATERIAL IS WATER BASE AND DRYING TIME IS DEPENDENT ON HUMIDITY. MANUFACTURER'S REP SAYS THAT IF YOU HAVE A PROBLEM WITH EXTREMELY HIGH HUMIDITY WHICH WOULD SUBSTANTIALLY AFFECT COMPLETE DRYING THAT YOU SHOULD NOT USE JENNITE.

S E C R E T

CFN: [] A 220 JENNITE J-16 55 J-220 INFO NOT AVAILABLE A NOT USUALLY A A 300 SQ FT 24 SQUEEGEES 100 FT SQ PER 24 HRS REPA NOT USE BT

25X1A

1. Build laundry Bldg on No. side of Porta Kamp trailers off shower room large enough to accommodate 3 automatic washers and one drier for the exclusive use of

personnel. Equip Bldg with two automatic washers and one drier. Erect clothes lines behind laundry Bldg approx 50' between outer poles and one pole in middle. Crossbars on all poles so that 3 to 4 lengths of line may be strung between poles.

2. Replace present 3 washers in existing wash house South of TANK billeting/mess area with 4 automatic washers plus two driers. Ironing facilities should be included. A mangle would suffice for flat work but a steam iron should be used on shirts and articles of that nature. This facility should be manned by someone capable of washing and ironing clothes, bedding and other linens in a satisfactory manner on a 5 day a week schedule. For those personnel desiring to wash their own

clothes, the facility would be available after 1700 daily and on Saturday and Sundays.